Operator Training Simulation (IEC)

Improve Staff Skills with Power System Digital Twin Simulation Training

EcoStruxure Power Digital Application

ESXP2GE003EN-05 11/2023

Eco**G**truxure[®] Power





Legal Information

The information provided in this document contains general descriptions, technical characteristics and/or recommendations related to products/solutions.

This document is not intended as a substitute for a detailed study or operational and site-specific development or schematic plan. It is not to be used for determining suitability or reliability of the products/solutions for specific user applications. It is the duty of any such user to perform or have any professional expert of its choice (integrator, specifier or the like) perform the appropriate and comprehensive risk analysis, evaluation and testing of the products/solutions with respect to the relevant specific application or use thereof.

The Schneider Electric brand and any trademarks of Schneider Electric SE and its subsidiaries referred to in this document are the property of Schneider Electric SE or its subsidiaries. All other brands may be trademarks of their respective owner.

This document and its content are protected under applicable copyright laws and provided for informative use only. No part of this document may be reproduced or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), for any purpose, without the prior written permission of Schneider Electric.

Schneider Electric does not grant any right or license for commercial use of the document or its content, except for a non-exclusive and personal license to consult it on an "as is" basis.

Schneider Electric reserves the right to make changes or updates with respect to or in the content of this document or the format thereof, at any time without notice.

To the extent permitted by applicable law, no responsibility or liability is assumed by Schneider Electric and its subsidiaries for any errors or omissions in the informational content of this document, as well as any non-intended use or misuse of the content thereof.

AccuSine[™], Acti 9[™], Altivar[™], ASCO[™], BlokSeT[™], ComPacT[™], EcoStruxure[™], EnerLin'X[™], ETAP[™], EVlink[™], EvoPacT[™], Galaxy[™], Harmony[™], Iso-Gard[™], Masterclad[™], MasterPacT[™], MicroLogic[™], Modicon[™], Okken[™], PowerLink[™], PowerLogic[™], PowerPacT[™], Power-Zone[™], PremSeT[™], PrismaSeT[™], Schneider Electric[™], SM AirSeT[™], Square D[™], SureSeT[™], TeSys[™], TransferPacT[™], Trihal[™], and Vigilohm[™] are trademarks and the property of Schneider Electric SE, its subsidiaries, and affiliated companies. All other trademarks (Cyber Sciences[™], Hirschmann[™]) are the property of their respective owners.

Table of Contents

Overview	5
Context of Application	5
Application Outcomes	6
Electrical Architecture	7
Digital Architecture	8
System Description	9
Data Flow	9
Inputs	9
Data Recording and Timestamping	
Time Synchronization	
Data Processing	
Outputs	12

Overview

Context of Application

Modern electrical systems are increasingly complex to operate in particular with the advent of renewable power sources. For operation and maintenance personnel, it is significantly more challenging to master all operational and maintenance tasks, especially when performed in stressful situations. Insufficient knowledge to perform certain operations or procedures can result in delayed restoration following an unintended event, or lead to safety consequences.

Problem to Solve

The facility, operations, and maintenance managers need to:

- · Avoid unplanned outages and reduce safety risks due to operator missteps.
- · Overcome skill shortages in operations and maintenance teams.
- Strengthen operator confidence and efficiency to perform complex operations (such as startup and shutdown).
- · Enable operators to practice safely without affecting the live system.

Purpose of the Application

Provide an efficient and cost-effective training tool for operations and maintenance staff to help reduce safety risks

Use a highly-realistic model-driven power system simulator (Digital Twin) to:

- Improve familiarity with day-to-day and/or complex operations in offline system (predefined scenarios).
- Track and review trainee actions and identify potential areas for staff skills improvement.
- Improve response time to critical events.



Operator Training Simulator

Application Outcomes

Real-Time Dynamic Simulation

Model-driven real-time simulator using a complete set of actual data of the entire electrical network to mimic a multitude of user-defined real-case scenarios and to train operators.



Schematic Diagram for Operator Training Simulation Application

Live Data Display

- Digital single-line diagrams with real-time animation of the status of the electrical network
- Real-time electrical data and equipment status

Reports

 Trainee reports: track and review trainee actions to identify potential areas for improvement.

Electrical Architecture

The following diagram details the areas of the architecture where the connected products should be installed in order to implement the Operator Training Simulation application:



* DSB = Distribution Switchboard

Digital Architecture

The digital architecture of the Operator Training Simulation application involves collecting the input data from the different products, either directly over Ethernet or via gateways. This data is then processed by the Edge Control (EcoStruxure Power Operation) live environment and passed on to the ETAP Simulation Engine (using the OPC UA communication protocol) for training or simulations in simulated Edge Control environments.

The recommended digital architecture for the application is shown below:



* Depending on the connected device chosen, communication protocols can be Ethernet or Serial

Ethernet - technical LAN

Wireless - 2.4 GHz

Serial

System Description

Data Flow

The Operator Training Simulation application can be broken down as follows:



Inputs

The Operator Training Simulation application collects data in real time from the connected products of the electrical installation to generate a highly realistic model of the electrical system and enable operators to be trained on a digital twin of a site.

Electrical measurements and status information can be acquired from a wide range of connected products as well as third-party equipment through open communication protocols. Typical connected products include:

• Energy/Power meters, such as PowerLogic ION9000, PM8000, PM5000, HDPM6000, Acti9 iEM3000, PowerTag







PowerLogic ION9000

PowerLogic

HDPM6000

PowerLogic PM8000

PowerLogic PM5000







PowerLogic PowerTag

 Protection devices, such as PowerLogic P5/P3, MasterPacT MTZ, ComPacT NSX (including its wireless auxiliary contact), Acti9 Active



PowerLogic P5



P3

Acti9

iEM3000

MasterPacT

MTZ





ComPacT NSX and Auxiliary Contact

Acti9 Active

....

Other equipment, such as UPS (Galaxy VX/VL/VM/VS), ATS/PTS (ASCO • 7000 Series PTS, TransferPacT Active Automatic), ATS controller (PowerLogic T300), protective devices (ASCO SPD with ASM), power correction devices (PowerLogic PFC and AccuSine PCS+/PCSn/EVC/PFV+), Load Banks







Galaxy VX/VL/VM/VS 7000 Series PTS



PowerLogic

T300



ASCO SPD with ASM

PowerLogic PowerLogic AccuSine PCS

+/PCSn/ EVC/PFV+



Load Banks

Electrical Measurements

The following electrical measurements are collected from connected products (real-time values, the minimum, maximum and average value):

- Current and voltage •
- Power (Active, Reactive, Apparent)

PFC

- Frequency
- Energy
- Harmonic distortion
- Voltage and current unbalance

Status of Electrical Equipment

Information is collected from intelligent electrical devices such as circuit breakers, power quality correction equipment, ATSs and other electrical distribution equipment:

- Circuit breaker position (open, closed, racked-in, racked-out, etc.)
- Circuit breaker trip status, protection status •
- UPS status, motor status
- Other statuses, operating modes or conditions

User Controls

Trainees can interact with the digital twin and follow operational procedures by evaluating control strategies and emulate controls such as:

- Sequence of operations
- Load transfer switching
- Contingency plans

ETAP Intelligent Single-Line Diagram (iSLD)

ETAP's iSLD is a digital representation of the electrical system including all equipment characteristics and system behavior. It is designed to be the model of AC & DC networks based on real-time and estimated data.

"What If" Operating Scenarios

Some sequences of events must be predefined to train operators on sequences following critical operational situations such as:

- Utility outage
- Generator testing
- Motor starting
- Faults
- Contingency plans
- · Sequence of operations to restore the power

Data Recording and Timestamping

For the Operator Training Simulation application:

- User actions are recorded and timestamped by EcoStruxure Power Operation.
- Status changes generated in response by the ETAP Simulation Engine are recorded and timestamped by the ETAP server.

This timestamped data is used to provide accurate sequence of events in the action summary report that can be produced after training sessions or after simulated actions.

To reach an optimal chronological correlation, a time accuracy of ± 1 millisecond is recommended for both the trainee workstation (EcoStruxure Power Operation) and the ETAP Simulation Engine.

For a comprehensive overview of device recording and timestamping capabilities, refer to Data Recording and Time Synchronization Capabilities of EcoStruxure Power Connected Products.



ETAP Simulation Engine



EcoStruxure Power Operation

Time Synchronization

To be able to replay or analyze sequence of operations, time synchronization is required between the EcoStruxure Power Operation computers (server and user HMI) and the ETAP Simulation Engine.

This can be achieved by setting NTP or SNTP synchronization between computers.



Data Processing

Real-time data from the electrical installation is provided by EcoStruxure Power Operation Edge Control using OPC UA communication protocol.

ETAP Simulation Engine additionally analyzes power system dynamics and transient disturbances, estimates the magnitudes and phase angles of bus voltages, currents, and performs analysis on arc flash hazards and incident energy.

This data is used by the ETAP Simulation Engine to generate highly-realistic equipment responses to a series of control actions by a user.

All user actions (user controls) are logged for traceability purposes.



Simulation Engine



EcoStruxure Power Operation

Outputs

The outputs of the ETAP Simulation Engine are displayed in EcoStruxure Power Operation.





Real-time Dynamic Simulation

Electrical SCADA utilizes data generated by ETAP Simulation Engine to mimic a multitude of user-defined real-case scenarios. It helps to provide an advanced and

cost-effective training environment, that prepares operators to quickly respond to various power systems events and emergency situations.



Simulated Operator Training Environment

Live Data Display

The live status of the electrical distribution can be represented in the Edge Control software (EcoStruxure Power Operation) in various forms such as:

- Digital single-line diagrams, with real-time animation of the status of the electrical network
- · Real-time electrical data and equipment status

Reports

In addition to specialized reports, action summary reports are generated to evaluate the steps taken by operators, and to assess and/or validate their competence level.

inine .				ETAP		Two	1
-		21.1.00					11-22-2022
ORDER						514	SEINNOWNAM
aginese.						Revision:	Bast
losans:	Innovation Lab V2			and a second of		Coafig.	Normal
				Action Summery			
	Louis ID	Time (Sec.)	Device Type	Deta D	Adm		
	Load Fire	0.000	Nee		Lond Flow		
		655.000		19,54,8e5,08	Com		
		662.000		DV MARK BALL CB	Open		
		462.300		DV_FREEBER_CB	Clear		
		479.330		DV_File_Biol_CB	Open		
		684.330		Dury B. Ne. CB	Ches		
		mag 330		country med (28	Cire		
		201 100		IN Stational Co.	Citem		
		76.10		19 Date Bar Ch	Case		
		711.000		INA TA TORI OD	Contra Co		
		711.000		HEA DA FERZ CD	Ore		
		725.300		UN For Mel CB	Gene		
		154.000		LV For Net (D)	Course.		
		199.300		LV_Fit_Bird_CB	Cem		
		784,930		LV_For_Ned_CB	Open		
		754,300		UV_For_NetLCB	Cyan.		
		755.100		PEA DA MAIN CB	Clew		
		758.200		Some Nettal	Open		
		758,390		Source, Emergency	Clew		
		771,500		LY_UnityB_Dir_CD	Orm		
		115.300		DV_UNION_DM_CD	Open		
		785.300		DV MARK BALLOR	Clear		
		100.000		the local day of	- fee		
		1015.000		PER DR. MADY CD.			
		1015.010		Some Terration	Com.		
		105.500		Some Name	0.0		
		105.00		LV For Here CD	Orm		
		1010.300		LN Fig Bac (D)	Own		
		1005.000		IV In Inc. (D.	-		

ETAP Action Summary Report

Schneider Electric 35 rue Joseph Monier 92500 Rueil Malmaison France

+ 33 (0) 1 41 29 70 00

www.se.com

As standards, specifications, and design change from time to time, please ask for confirmation of the information given in this publication.

© 2023 Schneider Electric. All rights reserved.

ESXP2GE005EN-05